

ENFORCER Products, Inc. P.O. Box 1060 Cartersville, GA 30120 1-888-805-HELP

Material Safety Data Sheet

and Safe Handling and Disposal Information

Section 1. Chemical Product and Company Identification

Product Name Oven and Grill Cleaner

Product Code HD0271-24 CN0271-24

Formula No. 0210

Date of issue 03/27/03 Supersedes 02/28/02

Emergency telephone number **For MSDS Information:**

Compliance Services (404) 352-1680

For a Medical Emergency:

INFOTRAC

(877) 541-2016 (Toll Free - Calls Recorded)

For a Transportation Emergency:

CHEMTREC

(800) 424-9300 (Toll Free - Calls Recorded)

Prepared by Compliance Services Group

Acuity Specialty Products Group 1420 Seaboard Industrial Blvd.

Atlanta, GA 30318

Section 2. Composition, Information on Ingredients

Name of Hazardous Ingredients	CAS#	% by Weight	Exposure Limits
1) POTASSIUM HYDROXIDE; caustic potash; lye	1310-58-3	0-5	ACGIH /OSHA (United States). CEIL: 2 mg/m ³
2) ETHYLENE GLYCOL MONOBUTYL ETHER; 2-butoxyethanol; butyl cellosolve	111-76-2	0-5	ACGIH TLV (United States). Skin TWA: 20 ppm Form: Vapor OSHA PEL (United States). Skin
3) MONOETHANOLAMINE; 2-aminoethanol; MEA	141-43-5	0-5	TWA: 25 ppm Form: Vapor OSHA PEL (United States). TWA: 3 ppm
4) BLEND OF ISOBUTANE, PROPANE & n-BUTANE	75-28-5; 74-98-6; 106-97-8	0-5	ACGIH TLV (United States). STEL: 6 ppm ACGIH TLV (United States). TWA: 800 ppm OSHA PEL (United States). TWA: 1000 ppm

Section 3. Hazards Identification

Acute Effects

Routes of Entry Absorbed through skin. Eye contact. Inhalation. Ingestion.

Eyes Hazardous in case of eye contact (corrosive).

Skin Hazardous in case of skin contact (corrosive, permeator). Skin contact may produce burns. Harmful if absorbed through the skin.

Inhalation Hazardous in case of inhalation (lung corrosive). Inhalation of the spray mist may produce severe irritation of respiratory tract, characterized by coughing, choking, or shortness of breath.

Ingestion May be fatal if swallowed. May cause burns to mouth, throat, and stomach.

Chronic Effects The substance may be toxic to blood, kidneys, liver. Repeated or prolonged exposure to the substance can produce target organs damage. Repeated or prolonged contact with spray mist may produce chronic eye irritation and severe skin irritation. Repeated or prolonged exposure to spray mist may produce respiratory tract irritation leading to frequent attacks of bronchial infection.

Carcinogenic Effects Ingredients: Not listed as carcinogen by OSHA, NTP or IARC.

See Toxicological Information (section 11)



Section 4. First Aid Measures

Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. **Eye Contact**

Get medical attention immediately.

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and **Skin Contact**

shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical **Inhalation**

attention immediately.

If swallowed, do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an **Ingestion**

unconscious person. Get medical attention immediately.

Section 5. Fire Fighting Measures

Flash Point Not applicable. Flammable Limits Not applicable.

Flammability Non-flammable. (CSMA) Fire Hazard Not applicable.

SMALL FIRE: Use DRY chemical powder. **Fire-Fighting Procedures**

LARGE FIRE: Use water spray, fog or foam. Do not use water jet.



Section 6. Accidental Release Measures

Spill Clean up Unlikely in this form

Section 7. Handling and Storage

Handling Avoid prolonged contact with eyes, skin, and clothing. Avoid contact with eyes. Do not ingest. Do not breathe vapor or mist.

Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.

Storage Keep container tightly closed. Keep container in a cool, well-ventilated area. Store below 120°F.

Section 8. Exposure Controls, Personal Protection

Personal Protection

Eyes Chemical splash goggles.

Body Synthetic apron. Use chemical resistant, impervious gloves.

Use with adequate ventilation. A respirator is not needed under normal **Respiratory**

and intended conditions of product use.

Protective Clothing (Pictograms)







Section 9. Physical and Chemical Properties

Grayish white. **Physical State** Liquid. Color 13.0 - 14.0 Butyl pH **Odor Boiling Point** 100°C (212°F) **Vapor Pressure** Not available. **Specific Gravity** 1.43 (Water = 1)**Vapor Density** Not available. VOC (Consumer) 114 (g/l). <1 compared to Water **Evaporation Rate**

Solubility Easily soluble in cold water, hot water.

Section 10. Stability and Reactivity

Stability and Reactivity The product is stable.

Incompatibility Reactive with oxidizing agents, acids.

Hazardous Decomposition Products These products are carbon oxides (CO, CO2) and nitrogen oxides (NO, NO2...)

Hazardous Polymerization Will not occur.

Section 11. Toxicological Information

Toxicity to Animals Ethylene glycol monobutyl ether:

ORAL (LD50): Acute: 1746 mg/kg [Rat].

Monoethanolamine:

Acute: 2100 mg/kg [Rat.]. ORAL (LD50): DERMAL (LD50): Acute: 1000 mg/kg [Rabbit.].

Blend of Isobutane, Propane, and n-Butane

LD50: Not available. LC50: Not available. Potassium hydroxide:

ORAL (LD50): Acute: 365 mg/kg [Rat.].

Section 12. Ecological Information

Ecotoxicity Not available.

Biodegradable/OECD Not available.

Section 13. Disposal Considerations

Waste Information Waste must be disposed of in accordance with federal, state and local environmental control regulations.

Waste Stream D002 Consult your local or regional authorities.

Section 14. Transport Information

Proper shipping name Consumer Commodity

DOT ClassificationORM-DUN numberNot applicable.

TDG Classification ORM-D

Section 15. Regulatory Information

U.S. Federal Regulations SARA 313 toxic chemical notification and release reporting: Ethylene glycol monobutyl ether

Clean Water Act (CWA) 311: Potassium hydroxide

Clean air act (CAA) 112 regulated toxic substances: Ethylene glycol monobutyl ether

State Regulations California prop. 65: No products were found.

WHMIS (Canada) CLASS D-1B: Material causing immediate and serious toxic effects (TOXIC).

CLASS E: Corrosive liquid.

Section 16. Other Information

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.