



Specializing in Materials Management

SAFETY DATA SHEET.

Issuing date 17-Dec-2014

Revision Date 17-Dec-2014

Version 1.03

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name 80-925 INTER-LUBE DELAYED VISCOSITY PENETRATING GREASE

Recommended use of the chemical and restrictions on use

Product code F00480

Product Type Extremely flammable aerosol
Synonyms None

Supplier's details

Recommended Use Lubricant.
Uses advised against No information available

Manufactured For:
Kimball Midwest
4800 Roberts Rd.
Columbus, OH 43228

Emergency telephone number
Chemical Emergency Phone Number Chemtrec 1-800-424-9300
Company Emergency Phone Number 1-800-233-1294

2. HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Compressed Gas

GHS Label elements, including precautionary statements

Emergency Overview

DANGER

Hazard Statements

Causes skin irritation
Causes serious eye irritation
Suspected of damaging fertility or the unborn child
May cause drowsiness or dizziness
May cause damage to organs (central nervous system and respiratory system) through prolonged or repeated exposure.
May be fatal if swallowed and enters airways
Extremely flammable aerosol
Contains gas under pressure; may explode if heated



Appearance Hazy

Physical state Aerosol

Odor Solvent

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Wear protective gloves/protective clothing/eye protection/face protection
Wash face, hands and any exposed skin thoroughly after handling
Do not breathe dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Keep away from heat/sparks/open flames/hot surfaces. — No smoking
Do not spray on an open flame or other ignition source
Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention
IF ON SKIN: Wash with plenty of soap and water.
If skin irritation occurs: Get medical advice/attention
Take off contaminated clothing and wash before reuse
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER or doctor/physician if you feel unwell

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

None

Other information

- Toxic to aquatic life with long lasting effects

0.00001336% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS # 110-54-3, HEXANE, MAY BE SUBSTITUTED FOR CAS # 64742-49-0, COMMERCIAL HEXANES.

Chemical Name	CAS-No	Weight %*
HEXANE	110-54-3	20-30
PROPANE/ISOBUTANE/N-BUTANE	68476-86-8	20-30
ACETONE	67-64-1	10-20
NONYLPHENOXYPOLYETHOXYETHANOL	127087-87-0	1-10
POLYTETRAFLUOROETHYLENE	9002-84-0	0.1-1.0

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures for different exposure routes

General advice	Avoid contact with skin, eyes, and clothing. Avoid breathing, vapors, mist, or gas.
Eye contact	Rinse immediately with plenty of water and seek medical advice.
Skin contact	Wash off immediately with soap and plenty of water. If skin irritation persists, call a physician.
Inhalation	Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped, contact emergency medical services immediately.
Ingestion	Do NOT induce vomiting. Call a physician immediately. Never give anything by mouth to an unconscious person. Risk of product entering the lungs on vomiting after ingestion.

Most important symptoms/effects, acute and delayed

Main Symptoms May cause skin irritation. Drowsiness. Dizziness. Difficulty breathing.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

water fog. Dry chemical. Carbon dioxide (CO2). Cool containers / tanks with water spray.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Flammable or extremely flammable aerosol. Container may burst in fire.

Explosion Data

Sensitivity to Mechanical Impact none.

Sensitivity to Static Discharge Yes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation.

Environmental precautions

Environmental precautions Report spills as required by local and federal regulations.

Methods and materials for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Contain liquid and collect with an inter,non-combustible material.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top of can. Avoid skin contact. Use with adequate ventilation. Keep container away from heat, flames, and all other sources of ignition. Keep can away from all sources of electricity such as electric motors and batteries. Do not spray on hot surfaces.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions Keep containers tightly closed in a dry, cool and well-ventilated place.

Incompatible products Store away from strong oxidizers and acids.

Aerosol Level 3

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
HEXANE 110-54-3	TWA: 50 ppm Skin - potential significant contribution to overall exposure by the cutaneous route	TWA: 500 ppm TWA: 1800 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 180 mg/m ³	IDLH: 1100 ppm TWA: 50 ppm TWA: 180 mg/m ³
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	74-98-6: TWA: 1000 ppm 106-97-8: STEL: 1000 ppm 75-28-5: STEL: 1000 ppm	74-98-6: TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³ 106-97-8: (vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³	74-98-6: IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³ 106-97-8: TWA: 800 ppm TWA: 1900 mg/m ³ 75-28-5: TWA: 800 ppm TWA: 1900 mg/m ³
ACETONE 67-64-1	STEL: 750 ppm TWA: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m ³

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration)

NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Exposure controls**Engineering Measures**

Ventilation systems. Use adequate ventilation to keep the exposure levels below the OELs.

Individual protection measures, such as personal protective equipment**Eye/Face Protection**

Safety glasses with side-shields.

Skin and body protection

Chemical resistant apron. Protective gloves.

Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES**Physical and chemical properties****Physical state**

Aerosol

Appearance

Hazy

Color

Light Amber

Odor

Solvent

Odor Threshold

No information available

Property**Values****Remarks • Methods****pH**

No information available

Melting/freezing point

No information available

Boiling point/boiling range

No information available

Flash Point

-96.4 °C / -141 °F

Based on propellant

Evaporation rate	No information available
Flammability (solid, gas)	No information available
Flammability Limits in Air	
upper flammability limit	No information available
lower flammability limit	No information available
Vapor pressure	No information available
Vapor density	No information available
Specific Gravity	0.728
Water solubility	Practically insoluble
Partition coefficient: n-octanol/water	No information available
Autoignition temperature	No information available
Decomposition temperature	No information available
Viscosity	No information available
Explosive properties	No information available

Other information

VOC Content(%) 48.54

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Extremes of temperature and direct sunlight.

Incompatible Materials

Store away from strong oxidizers and acids.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	Product does not present an acute toxicity hazard based on known information
Inhalation	Exposure to high vapour concentrations may cause nervous systems effects such as headache, nausea, and dizziness.
Eye contact	May cause slight irritation.
Skin contact	Irritating to skin. Prolonged skin contact may defat the skin and produce dermatitis.
Ingestion	Not acutely toxic. Aspiration into the lungs during swallowing may cause serious lung damage which may be fatal.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
HEXANE 110-54-3	-	= 3000 mg/kg (Rabbit)	= 48000 ppm (Rat) 4 h
ACETONE 67-64-1	-	20,000 mg/kg (Rabbit)	= 50100 mg/m ³ (Rat) 8 h

NONYLPHENOXYPOLYETHOXYE THANOL 127087-87-0	= 1310 mg/kg (Rat)	-	-
--	----------------------	---	---

Information on toxicological effects

Symptoms Symptoms of overexposure may be headache, dizziness, tiredness, nausea, and vomiting. May cause mild irritation. Irritating to skin. Prolonged or repeated exposure may cause dermatitis. Not acutely toxic. Aspiration into the lungs during swallowing may cause serious lung damage which may be fatal.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Irritating to skin.
Eye damage/irritation Irritating to eyes.
Sensitization No information available.
Germ Cell Mutagenicity No information available.
Carcinogenicity The table below indicates whether each agency has evaluated a listed ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
POLYTETRAFLUOROETHYLENE 9002-84-0	-	Group 3	-	-

ACGIH: (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive toxicity Suspected of damaging fertility or the unborn child.
Specific target organ systemic toxicity (single exposure) May cause drowsiness and dizziness.
Specific target organ systemic toxicity (repeated exposure) Causes damage to organs through prolonged or repeated exposure.
Chronic toxicity Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential cardiac arrest. Prolonged skin contact may defat the skin and produce dermatitis.
Target Organ Effects Central nervous system, Eyes, Peripheral Nervous System (PNS), Respiratory system, Skin.
Aspiration hazard May be fatal if swallowed and enters airways.

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity 0.00001336% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 2276 mg/kg

ATEmix (dermal) 5007 mg/kg

ATEmix (inhalation-dust/mist) 510.9 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
HEXANE 110-54-3	-	2.1 - 2.98 mg/L LC50 Pimephales promelas 96h flow-through	-	-
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	-	-	-	-

**F00480 - 80-925 INTER-LUBE DELAYED VISCOSITY
PENETRATING GREASE**

Revision Date 17-Dec-2014

ACETONE 67-64-1	-	4.74 - 6.33 mL/L LC50 Oncorhynchus mykiss 96h 6210 - 8120 mg/L LC50 Pimephales promelas 96h static 8300 mg/L LC50 Lepomis macrochirus 96h	-	10294 - 17704 mg/L EC50 Daphnia magna 48h Static 12600 - 12700 mg/L EC50 Daphnia magna 48h
--------------------	---	--	---	---

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	log Pow
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	2.8
ACETONE 67-64-1	-0.24

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste Disposal Methods

Dispose of in accordance with federal, state, and local regulations.

Contaminated packaging

Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOT Ground

CONSUMER COMMODITY ORM-D
or
LIMITED QUANTITY

IATA

UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.

IMDG

UN1950, AEROSOLS, 2.1, LTD. QTY.

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
HEXANE	X	X	X	X	X	X	X	X
PROPANE/ISOBUTANE/N-BUTANE	X	X	X	Not listed	X	X	X	X
ACETONE	X	X	X	X	X	X	X	X
NONYLPHENOXYPOLYETHOXYETHANOL	X	X	X	X	X	X	X	X

**F00480 - 80-925 INTER-LUBE DELAYED VISCOSITY
PENETRATING GREASE**

Revision Date 17-Dec-2014

POLYTETRAFLUORO ETHYLENE	X	X	Not listed	X	X	X	X	X
-----------------------------	---	---	------------	---	---	---	---	---

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %
HEXANE - 110-54-3	110-54-3	20-30	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	no

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
HEXANE 110-54-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
ACETONE 67-64-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

U.S. State Regulations

California Proposition 65

No warning required.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
HEXANE 110-54-3	X	X	X
ACETONE 67-64-1	X	X	X
POLYTETRAFLUOROETHYLENE 9002-84-0			X

EPA Pesticide Registration Number Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

16. OTHER INFORMATION

<u>NFPA</u>	Health Hazard 2	Flammability 4	Instability 0	Physical and chemical hazards -
<u>HMIS</u>	Health Hazard 2*	Flammability 4	Physical Hazard 1	Personal protection B
<i>Chronic Hazard Star Legend</i>	<i>Chronic Health Hazard Repeated or prolonged exposure may cause central nervous system damage</i>			

Prepared By	Regulatory Affairs
Issuing date	17-Dec-2014
Revision Date	17-Dec-2014

Revision Note

No information available

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet